## Transition from GCSE to A Level

Moving from GCSE Science to A Level can be a daunting leap. You'll be expected to remember a lot more facts, equations, and definitions, and you will need to learn new maths skills and develop confidence in applying what you already know to unfamiliar situations.

This worksheet aims to give you a head start by helping you:

- · to pre-learn some useful knowledge from the first chapters of your A Level course
- understand and practise of some of the maths skills you'll need.

## Learning objectives

After completing the worksheet you should be able to:

- define practical science key terms
- · recall the answers to the retrieval questions
- · perform maths skills including:
  - o unit conversions
  - o uncertainties
  - using standard form and significant figures
  - resolving vectors
  - rearranging equations
  - o equations of work, power, and efficiency.

1

# **Retrieval questions**

You need to be confident about the definitions of terms that describe measurements and results in A Level Physics.

Learn the answers to the questions below then cover the answers column with a piece of paper and write as many answers as you can. Check and repeat.

## Practical science key terms

When is a measurement valid?	when it measures what it is supposed to be measuring	
When is a result accurate?	when it is close to the true value	
What are precise results?	when repeat measurements are consistent/agree closely with each other	
	how precise repeated measurements are when they are taken	
What is repeatability?	by the same person, using the same equipment, under the	
	same conditions	
VAVI A i	how precise repeated measurements are when they are taken	
What is reproducibility?	by different people, using different equipment	
What is the uncertainty of a measurement?	the interval within which the true value is expected to lie	
Define measurement error	·	
What type of error is caused by results varying	wan dana awar	
around the true value in an unpredictable way?	random error	
VA/In at in a prostore ation array?	a consistent difference between the measured values and true	
What is a systematic error?	values	
What does zero error mean?	a measuring instrument gives a false reading when the true	
what does zero error mean?	value should be zero	
Which variable is changed or selected by the	independent veriable	
investigator?	independent variable	
What is a dependent variable?	a variable that is measured every time the independent	
viriat is a dependent variable?	variable is changed	
Define a fair test	a test in which only the independent variable is allowed to	
Definite a fail test	affect the dependent variable	
What are control variables?	variables that should be kept constant to avoid them affecting	
Wilat are control variables:	the dependent variable	

# **Foundations of Physics**

Learn the answers to the questions below then cover the answers column with a piece of paper and write as many answers as you can. Check and repeat.

What is a physical quantity?	a property of an object or of a phenomenon that can be measured	
What are the S.I. units of mass, length, and time?	kilogram (kg), metre (m), second (s)	
What base quantities do the S.I. units A, K, and	current, temperature, amount of substance	
mol represent?	, , ,	
List the prefixes, their symbols and their	pico (p) 10 <sup>-12</sup> , nano (n) 10 <sup>-9</sup> , micro (μ) 10 <sup>-6</sup> , milli (m) 10 <sup>-3</sup> , centi	
multiplication factors from pico to tera (in order of	(c) $10^{-2}$ , deci (d) $10^{-1}$ , kilo (k) $10^{3}$ , mega (M) $10^{6}$ , giga (G) $10^{9}$ ,	
increasing magnitude)	tera (T) 10 <sup>12</sup>	
What is a scalar quantity?	a quantity that has magnitude (size) but no direction	
What is a vector quantity?	a quantity that has magnitude (size) and direction	
What are the equations to resolve a force, F, into	$F_x = F \cos \theta$	
two perpendicular components, $F_x$ and $F_y$ ?	$F_y = F \sin \theta$	
What is the difference between distance and	distance is a scalar quantity	
displacement?	displacement is a vector quantity	
What does the Greek capital letter $\Delta$ (delta)	'change in'	
mean?		
What is the equation for average speed in	$v = \frac{\Delta x}{1}$	
algebraic form?	$v = \frac{\Delta x}{\Delta t}$	
What is instantaneous speed?	the speed of an object over a very short period of time	
What does the gradient of a displacement–time	e velocity	
graph tell you?		
How can you calculate acceleration and	acceleration is the gradient	
displacement from a velocity–time graph?	displacement is the area under the graph	
Write the equation for acceleration in algebraic	$a = \frac{\Delta v}{\Delta t}$	
form	$\Delta t = \Delta t$	
What do the letters suvat stand for in the	s = displacement, u = initial velocity, v = final velocity, a =	
equations of motion?	acceleration, $t = $ time taken	
Write the four <i>suvat</i> equations.	$v = u + at   s = ut + \frac{1}{2}at^2$	
	$s = \frac{1}{2}(u+v)t \qquad \qquad v^2 = u^2 + 2as$	
Define stopping distance	the total distance travelled from when the driver first sees a	
	reason to stop, to when the vehicle stops	
Define thinking distance	the distance travelled between the moment when you first see	
	a reason to stop to the moment when you use the brake	
Define braking distance		
	the vehicle stops	
What does free fall mean?	when an object is accelerating under gravity with no other force	
	acting on it	

### **Matter and radiation**

Learn the answers to the questions below then cover the answers column with a piece of paper and write as many answers as you can. Check and repeat.

· ·		
What is an atom made up of?	a positively charged nucleus containing protons and neutrons, surrounded by electrons	
Define a <i>nucleon</i>	a proton or a neutron in the nucleus	
What are the absolute charges of protons,	$+ 1.60 \times 10^{-19}$ , 0, and $- 1.60 \times 10^{-19}$ coulombs (C) respectively	
neutrons, and electrons?	+ 1.60×10 %, 0, and – 1.60×10 % coulombs (C) respectively	
What are the relative charges of protons,	1, 0, and – 1 respectively (charge relative to proton)	
neutrons, and electrons?	1, 0, and – Trespectively (charge relative to proton)	
What is the mass, in kilograms, of a proton, a	1.67×10 <sup>-27</sup> , 1.67×10 <sup>-27</sup> , and 9.11×10 <sup>-31</sup> kg respectively	
neutron, and an electron?	1.07×10, 1.07×10, and 9.11×10 kg respectively	
What are the relative masses of protons,	1, 1, and 0.0005 respectively (mass relative to proton)	
neutrons, and electrons?	1, 1, and 0.0000 respectively (mass relative to proton)	
What is the atomic number of an element?	the number of protons	
Define an isotope	isotopes are atoms with the same number of protons and	
Bellife di isotope	different numbers of neutrons	
Write what A, Z and X stand for in isotope	A: the number of nucleons (protons + neutrons)	
	Z: the number of protons	
notation ( <sup>A</sup> <sub>Z</sub> X)?	X: the chemical symbol	
Which term is used for each type of nucleus?	nuclide	
How do you calculate specific charge?	charge divided by mass (for a charged particle)	
What is the specific charge of a proton and an	9.58×10 <sup>7</sup> and 1.76×10 <sup>11</sup> C kg <sup>-1</sup> respectively	
electron?	Clock to take in oxio ong respectively	
Name the force that holds nuclei together	strong nuclear force	
What is the range of the strong nuclear force?	from 0.5 to 3–4 femtometres (fm)	
Name the three kinds of radiation	alpha, beta, and gamma	
What particle is released in alpha radiation?	an alpha particle, which comprises two protons and two neutrons	
Write the symbol of an alpha particle	4 <sub>2</sub> α	
What particle is released in beta radiation?	a fast-moving electron (a beta particle)	
Write the symbol for a beta particle	0 -1β	
Define <i>gamma radiation</i>	electromagnetic radiation emitted by an unstable nucleus	
What particles make up everything in the	matter and antimatter	
universe?	matter and antimatter	
Name the antimatter particles for electrons,	positron, antiproton, antineutron, and antineutrino respectively	
protons, neutrons, and neutrinos	position, antiproton, antinoation, and antinoatino respectively	
What happens when corresponding matter and	they annihilate (destroy each other)	
antimatter particles meet?	andy diminiate (destroy each exist)	
List the seven main parts of the electromagnetic	radio waves, microwaves, infrared, visible, ultraviolet, X-rays,	
spectrum from longest wavelength to shortest	gamma rays	
Write the equation for calculating the wavelength		
of electromagnetic radiation	wavelength $(\lambda) = \frac{\text{speed of light } (c)}{\text{frequency } (f)}$	
Define a photon	a packet of electromagnetic waves	
What is the speed of light?	3.00×10 <sup>8</sup> m s <sup>-1</sup>	
Write the equation for calculating photon energy	photon energy ( $E$ ) = Planck constant ( $h$ ) × frequency ( $f$ )	
Name the four fundamental interactions	gravity, electromagnetic, weak nuclear, strong nuclear	

## **Maths skills**

### 1 Measurements

#### 1.1 Base and derived SI units

Units are defined so that, for example, every scientist who measures a mass in kilograms uses the same size for the kilogram and gets the same value for the mass. Scientific measurement depends on standard units – most are *Système International* (SI) units. Every measurement must give the unit to have any meaning. You should know the correct unit for physical quantities.

#### Base units

Physical quantity	Unit	Symbol
length	metre	m
mass	kilogram	kg
time	second	s

Physical quantity	Unit	Symbol
electric current	ampere	А
temperature difference	Kelvin	K
amount of substance	mole	mol

#### **Derived units**

Example:

$$speed = \frac{distance\ travelled}{time\ taken}$$

If a car travels 2 metres in 2 seconds:

speed = 
$$\frac{2 \text{ metres}}{2 \text{ seconds}} = 1 \frac{\text{m}}{\text{s}} = 1 \text{m/s}$$

This defines the SI unit of speed to be 1 metre per second (m/s), or 1 m s<sup>-1</sup> (s<sup>-1</sup> =  $\frac{1}{s}$ ).

### **Practice questions**

1 Complete this table by filling in the missing units and symbols.

Physical quantity	Equation used to derive unit	Unit	Symbol and name (if there is one)
frequency	period <sup>-1</sup>	s <sup>-1</sup>	Hz, hertz
volume	length <sup>3</sup>		_
density	mass ÷ volume		_
acceleration	velocity ÷ time		-
force	mass × acceleration		
work and energy	force × distance		

### 1.2 Significant figures

When you use a calculator to work out a numerical answer, you know that this often results in a large number of decimal places and, in most cases, the final few digits are 'not significant'. It is important to record your data and your answers to calculations to a reasonable number of significant figures. Too many and your answer is claiming an accuracy that it does not have, too few and you are not showing the precision and care required in scientific analysis.

Numbers to 3 significant figures (3 s.f.):

(notice that the zeros before the figures and after the figures are *not* significant – they just show you how large the number is by the position of the decimal point).

Numbers to 3 significant figures where the zeros are significant:

207 4050 1.01 (any zeros between the other significant figures are significant).

Standard form numbers with 3 significant figures:

If the value you wanted to write to 3.s.f. was 590, then to show the zero was significant you would have to write:

590 (to 3.s.f.) or  $5.90 \times 10^2$ 

### **Practice questions**

**2** Give these measurements to 2 significant figures:

3 Use the equation:

$$resistance = \frac{potential difference}{current}$$

to calculate the resistance of a circuit when the potential difference is 12 V and the current is 1.8 mA. Write your answer in  $k\Omega$  to 3 s.f.

#### 1.3 Uncertainties

When a physical quantity is measured there will always be a small difference between the measured value and the true value. How important the difference is depends on the size of the measurement and the size of the uncertainty, so it is important to know this information when using data.

There are several possible reasons for uncertainty in measurements, including the difficulty of taking the measurement and the resolution of the measuring instrument (i.e. the size of the scale divisions).

For example, a length of 6.5 m measured with great care using a 10 m tape measure marked in mm would have an uncertainty of 2 mm and would be recorded as  $6.500 \pm 0.002$  m.

It is useful to quote these uncertainties as percentages.

For the above length, for example,

$$percentage\ uncertainty = \frac{uncertainty}{measurement} \times 100$$

percentage uncertainty = 
$$\frac{0.002}{6.500}$$
 × 100% = 0.03%. The measurement is 6.500 m ± 0.03%.

Values may also be quoted with absolute error rather than percentage uncertainty, for example, if the 6.5 m length is measured with a 5% error,

the absolute error =  $5/100 \times 6.5 \text{ m} = \pm 0.325 \text{ m}$ .

### **Practice questions**

Give these measurements with the uncertainty shown as a percentage (to 1 significant figure):

**a**  $5.7 \pm 0.1$  cm

**b** 450  $\pm$  2 kg **c** 10.60  $\pm$  0.05 s **d** 366 000  $\pm$  1000 J

Give these measurements with the error shown as an absolute value:

**a** 1200 W ± 10%

**b** 330 000  $\Omega \pm 0.5\%$ 

Identify the measurement with the smallest percentage error. Show your working.

**B** 26 ± 5 mm **C** 516 ± 5 mm

**D**  $1400 \pm 5 \, \text{mm}$ 

## 2 Standard form and prefixes

When describing the structure of the Universe you have to use very large numbers. There are billions of galaxies and their average separation is about a million light years (ly). The Big Bang theory says that the Universe began expanding about 14 billion years ago. The Sun formed about 5 billion years ago. These numbers and larger numbers can be expressed in standard form and by using prefixes.

## 2.1 Standard form for large numbers

In standard form, the number is written with one digit in front of the decimal point and multiplied by the appropriate power of 10. For example:

The diameter of the Earth, for example, is 13 000 km.

 $13\ 000\ \text{km} = 1.3 \times 10\ 000\ \text{km} = 1.3 \times 10^4\ \text{km}$ .

The distance to the Andromeda galaxy is 2 200 000 light years = 2.2 × 1 000 000 ly = 2.2×10<sup>6</sup> lv.

### 2.2 Prefixes for large numbers

Prefixes are used with SI units (see Topic 1.1) when the value is very large or very small. They can be used instead of writing the number in standard form. For example:

- A kilowatt (1 kW) is a thousand watts, that is 1000 W or 103 W.
- A megawatt (1 MW) is a million watts, that is 1 000 000 W or 106 W.
- A gigawatt (1 GW) is a billion watts, that is 1 000 000 000 W or 109 W.

Prefix	Symbol	Value	
kilo	k	10 <sup>3</sup>	
mega	M	10 <sup>6</sup>	

Prefix	Symbol	Value	
giga	G	10 <sup>9</sup>	
tera	Т	10 <sup>12</sup>	

For example, Gansu Wind Farm in China has an output of 6.8×109 W. This can be written as 6800 MW or 6.8 GW.

### **Practice questions**

Give these measurements in standard form:

**a** 1350 W **b** 130 000 Pa  $c 696 \times 10^6 s$ 

**d**  $0.176 \times 10^{12} \,\mathrm{C \, kg^{-1}}$ 

The latent heat of vaporisation of water is 2 260 000 J/kg. Write this in:

a J/q

**b** kJ/kg

c MJ/kg

### 2.3 Standard form and prefixes for small numbers

At the other end of the scale, the diameter of an atom is about a tenth of a billionth of a metre. The particles that make up an atomic nucleus are much smaller. These measurements are represented using negative powers of ten and more prefixes. For example:

- The charge on an electron =  $1.6 \times 10^{-19}$  C.
- The mass of a neutron =  $0.01675 \times 10^{-25}$  kg =  $1.675 \times 10^{-27}$  kg (the decimal point has moved 2 places to the right).
- There are a billion nanometres in a metre, that is 1 000 000 000 nm = 1 m.
- There are a million micrometres in a metre, that is  $1\,000\,000\,\mu\text{m} = 1\,\text{m}$ .

Prefix	Symbol	Value
centi	С	10-2
milli	m	10 <sup>-3</sup>
micro	u	10-6

Prefix	Symbol	Value
nano	n	10 <sup>-9</sup>
pico	р	10 <sup>-12</sup>
femto	f	10 <sup>-15</sup>

#### Practice questions

- Give these measurements in standard form:
  - $a \cdot 0.0025 \text{ m}$   $b \cdot 160 \times 10^{-17} \text{ m}$   $c \cdot 0.01 \times 10^{-6} \text{ J}$   $d \cdot 0.005 \times 10^{6} \text{ m}$   $e \cdot 0.00062 \times 10^{3} \text{ N}$

8

- Write the measurements for question 3a, c, and d above using suitable prefixes.
- Write the following measurements using suitable prefixes.
  - a a microwave wavelength = 0.009 m
  - **b** a wavelength of infrared =  $1 \times 10^{-5}$  m
  - **c** a wavelength of blue light =  $4.7 \times 10^{-7}$  m

#### 2.4 Powers of ten

When multiplying powers of ten, you must add the indices.

So  $100 \times 1000 = 100\ 000$  is the same as  $10^2 \times 10^3 = 10^{2+3} = 10^5$ 

When dividing powers of ten, you must subtract the indices.

So 
$$\frac{100}{1000} = \frac{1}{10} = 10^{-1}$$
 is the same as  $\frac{10^2}{10^3} = 10^{2-3} = 10^{-1}$ 

But you can only do this when the numbers with the indices are the same.

So 
$$10^2 \times 2^3 = 100 \times 8 = 800$$

And you can't do this when adding or subtracting.

$$10^2 + 10^3 = 100 + 1000 = 1100$$

$$10^2 - 10^3 = 100 - 1000 = -900$$

**Remember:** You can only add and subtract the indices when you are multiplying or dividing the numbers, not adding or subtracting them.

### **Practice questions**

- 6 Calculate the following values read the questions very carefully!
  - $a 20^6 + 10^{-3}$
  - **b**  $10^2 10^{-2}$
  - $c 2^3 \times 10^2$
  - **d**  $10^5 \div 10^2$
- 7 The speed of light is  $3.0 \times 10^8$  m s<sup>-1</sup>. Use the equation  $v = f\lambda$  (where  $\lambda$  is wavelength) to calculate the frequency of:
  - a ultraviolet, wavelength 3.0×10<sup>-7</sup> m
  - b radio waves, wavelength 1000 m
  - **c** X-rays, wavelength 1.0×10<sup>-10</sup> m.

## 3 Resolving vectors

#### 3.1 Vectors and scalars

**Vectors** have a magnitude (size) and a direction. Directions can be given as points of the compass, angles or words such as forwards, left or right. For example, 30 mph east and 50 km/h north-west are velocities.

**Scalars** have a magnitude, but no direction. For example, 10 m/s is a speed.

#### **Practice questions**

- 1 State whether each of these terms is a vector quantity or a scalar quantity: density, temperature, electrical resistance, energy, field strength, force, friction, frequency, mass, momentum, power, voltage, volume, weight, work done.
- 2 For the following data, state whether each is a vector or a scalar: 3 ms<sup>-1</sup>, +20 ms<sup>-1</sup>, 100 m NE, 50 km, −5 cm, 10 km S 30° W, 3 × 10<sup>8</sup> ms<sup>-1</sup> upwards, 273 °C, 50 kg, 3 A.

#### 3.2 Drawing vectors


Vectors are shown on drawings by a straight arrow. The arrow starts from the point where the vector is acting and shows its direction. The length of the vector represents the magnitude.

When you add vectors, for example two velocities or three forces, you must take the direction into account.

The combined effect of the vectors is called the resultant.

This diagram shows that walking 3 m from A to B and then turning through 30° and walking 2 m to C has the same effect as walking directly from A to C. AC is the resultant vector, denoted by the double arrowhead.

A careful drawing of a scale diagram allows us to measure these. Notice that if the vectors are combined by drawing them in the opposite order, AD and DC, these are the other two sides of the parallelogram and give the same resultant.



### **Practice questions**


3 Two tractors are pulling a log across a field. Tractor 1 is pulling north with force 1 = 5 kN and tractor 2 is pulling east with force 2 = 12 kN. By scale drawing, determine the resultant force.

### 3.3 Free body force diagrams


To combine forces, you can draw a similar diagram to the one above, where the lengths of the sides represent the magnitude of the force (e.g., 30 N and 20 N). The third side of the triangle shows us the magnitude and direction of the resultant force.

When solving problems, start by drawing a free body force diagram. The object is a small dot and the forces are shown as arrows that start on the dot and are drawn in the direction of the force. They don't have to be to scale, but it helps if the larger forces are shown to be larger. Look at this example.


A 16 kg mass is suspended from a hook in the ceiling and pulled to one side with a rope, as shown on the right. Sketch a free body force diagram for the mass and draw a triangle of forces.



Free body force diagram



Triangle of forces



Notice that each force starts from where the previous one ended and they join up to form a triangle with no resultant because the mass is in equilibrium (balanced).

#### Practice questions

- 4 Sketch a free body force diagram for the lamp (Figure 1, below) and draw a triangle of forces.
- 5 There are three forces on the jib of a tower crane (Figure 2, below). The tension in the cable T, the weight W, and a third force P acting at X.

The crane is in equilibrium. Sketch the triangle of forces.




Figure 1

Figure 2

### 3.4 Calculating resultants

When two forces are acting at right angles, the resultant can be calculated using Pythagoras's theorem and the trig functions: sine, cosine, and tangent.

For a right-angled triangle as shown:

$$h^2 = o^2 + a^2$$
  
 $\sin \theta = \frac{o}{h}$   
 $\cos \theta = \frac{a}{h}$   
 $\tan \theta = \frac{o}{a}$   
(soh-cah-toa). hypotenuse boopposite

## **Practice questions**

**6 Figure 3** shows three forces in equilibrium. Draw a triangle of forces to find T and α.

7 Find the resultant force for the following pairs of forces at right angles to each other:

**a** 3.0 N and 4.0 N **b** 5.0 N and 12.0 N




Figure 3

# 4 Rearranging equations

Sometimes you will need to rearrange an equation to calculate the answer to a question. For example, if you want to calculate the resistance R, the equation:

potential difference (V) = current (A) × resistance ( $\Omega$ ) or V = IR

must be rearranged to make R the subject of the equation:

$$R = \frac{V}{I}$$

When you are solving a problem:

- Write down the values you know and the ones you want to calculate.
- you can rearrange the equation first, and then substitute the values
   or
- substitute the values and then rearrange the equation

### 4.1 Substitute and rearrange

A student throws a ball vertically upwards at 5 m  $s^{-1}$ . When it comes down, she catches it at the same point. Calculate how high it goes.

Step 1: Known values are:

- initial velocity  $u = 5.0 \text{ m s}^{-1}$
- final velocity v = 0 (you know this because as it rises it will slow down, until it comes to a stop, and then it will start falling downwards)
- acceleration  $a = g = -9.81 \text{ m s}^{-2}$
- distance s = ?

**Physics** 

Step 2: Equation:

 $(final\ velocity)^2 - (initial\ velocity)^2 = 2 \times acceleration \times distance$ 

or 
$$v^2 - u^2 = 2 \times g \times s$$

Substituting:  $(0)^2 - (5.0 \text{ m s}^{-1})^2 = 2 \times -9.81 \text{ m s}^{-2} \times \text{s}$ 

$$0 - 25 = 2 \times -9.81 \times s$$

Step 3: Rearranging:

$$-19.62 s = -25$$

$$s = \frac{-25}{-19.62} = 1.27 \text{ m} = 1.3 \text{ m} (2 \text{ s.f.})$$

### **Practice questions**

- **1** The potential difference across a resistor is 12 V and the current through it is 0.25 A. Calculate its resistance.
- **2** Red light has a wavelength of 650 nm. Calculate its frequency. Write your answer in standard form.

(Speed of light = 
$$3.0 \times 10^8 \text{ m s}^{-1}$$
)

## 4.2 Rearrange and substitute

A 57 kg block falls from a height of 68 m. By considering the energy transferred, calculate its speed when it reaches the ground.

(Gravitational field strength = 10 N kg<sup>-1</sup>)

**Step 1:** 
$$m = 57 \text{ kg}$$
  $h = 68 \text{ m}$   $g = 10 \text{ N kg}^{-1}$   $v = ?$ 

Step 2: There are three equations:

$$PE = mgh$$
 KE gained =  $PE lost$  KE =  $0.5 m v^2$ 


Step 3: Rearrange the equations before substituting into it.

As KE gained = PE lost, 
$$m g h = 0.5 m v^2$$

You want to find v. Divide both sides of the equation by 0.5 m:

$$\frac{mgh}{0.5m} = \frac{0.5mv^2}{0.5m}$$

$$2 g h = v^2$$



To get v, take the square root of both sides:  $v = \sqrt{2gh}$ 

Step 4: Substitute into the equation:

$$v = \sqrt{2 \times 10 \times 68}$$
  
 $v = \sqrt{1360} = 37 \text{ m s}^{-1}$ 

### **Practice questions**

3 Calculate the specific latent heat of fusion for water from this data:

4.03×10<sup>4</sup> J of energy melted 120 g of ice.

Use the equation:

thermal energy for a change in state (J) = mass (kg) × specific latent heat (J kg<sup>-1</sup>) Give your answer in J kg<sup>-1</sup> in standard form.

## 5 Work done, power, and efficiency

#### 5.1 Work done

Work is done when energy is transferred. Work is done when a force makes something move. If work is done *by* an object its energy decreases and if work is done *on* an object its energy increases.

work done = energy transferred = force × distance

Work and energy are measured in joules (J) and are scalar quantities (see Topic 3.1).

### **Practice questions**

- 1 Calculate the work done when the resultant force on a car is 22 kN and it travels 2.0 km.
- 2 Calculate the distance travelled when 62.5 kJ of work is done applying a force of 500 N to an object.

#### 5.2 Power

Power is the rate of work done.

It is measured in watts (W) where 1 watt = 1 joule per second.

$$power = \frac{energy transferred}{time taken} or power = \frac{work done}{time taken}$$

 $P = \Delta W/\Delta t$   $\Delta$  is the symbol 'delta' and is used to mean a 'change in'

Look at this worked example, which uses the equation for potential energy gained.

A motor lifts a mass m of 12 kg through a height  $\Delta h$  of 25 m in 6.0 s.

Gravitational potential energy gained:

$$\Delta PE = mg\Delta h = (12 \text{ kg}) \times (9.81 \text{ m s}^{-2}) \times (25 \text{ m}) = 2943 \text{ J}$$

Power = 
$$\frac{2943 \text{ J}}{6.0 \text{ s}}$$
 = 490 W (2 s.f.)

### **Practice questions**

- 3 Calculate the power of a crane motor that lifts a weight of 260 000 N through 25 m in 48 s.
- 4 A motor rated at 8.0 kW lifts a 2500 N load 15 m in 5.0 s. Calculate the output power.

### 5.3 Efficiency

Whenever work is done, energy is transferred and some energy is transferred to other forms, for example, heat or sound. The efficiency is a measure of how much of the energy is transferred usefully.

Efficiency is a ratio and is given as a decimal fraction between 0 (all the energy is wasted) and 1 (all the energy is usefully transferred) or as a percentage between 0 and 100%. It is not possible for anything to be 100% efficient: some energy is always lost to the surroundings.

Efficiency = 
$$\frac{\text{useful energy output}}{\text{total energy input}}$$
 or Efficiency =  $\frac{\text{useful power output}}{\text{total power input}}$ 

(multiply by 100% for a percentage)

Look at this worked example.

A thermal power station uses 11 600 kWh of energy from fuel to generate electricity. A total of 4500 kWh of energy is output as electricity. Calculate the percentage of energy 'wasted' (dissipated in heating the surroundings).

You must calculate the energy wasted using the value for useful energy output:

percentage energy wasted = 
$$\frac{\text{(total energy input - energy output as electricity)}}{\text{total energy input}} \times 100$$
percentage energy wasted = 
$$\frac{\text{(11600 - 4500)}}{11600} \times 100 = 61.2\% = 61\% \text{ (2 s.f.)}$$

#### **Practice questions**

- 5 Calculate the percentage efficiency of a motor that does 8400 J of work to lift a load. The electrical energy supplied is 11 200 J.
- **6** An 850 W microwave oven has a power consumption of 1.2 kW. Calculate the efficiency, as a percentage.
- 7 Use your answer to question 4 above to calculate the percentage efficiency of the motor. (The motor, rated at 8.0 kW, lifts a 2500 N load 15 m in 5.0 s.)
- **8** Determine the time it takes for a 92% efficient 55 W electric motor take to lift a 15 N weight 2.5 m.

# Answers to maths skills practice questions

### 1 Measurements

1

Physical quantity	Equation used to derive unit	Unit	Symbol and name (if there is one)
frequency	period <sup>-1</sup>	s <sup>-1</sup>	Hz, hertz
volume	length <sup>3</sup>	m³	_
density	mass ÷ volume	kg m <sup>-3</sup>	_
acceleration	velocity ÷ time	m s <sup>-2</sup>	_
force	mass × acceleration	kg m s <sup>-2</sup>	N newton
work and energy	force × distance	N m (or kg m <sup>2</sup> s <sup>-2</sup> )	J joule

2 a 19 m b 21 s c 1.7 × 10<sup>-27</sup> kg d 5.0 s

**3** Resistance = 
$$\frac{12 \text{ V}}{1.8 \text{ mA}} = \frac{12 \text{ V}}{0.0018 \text{ A}} = 6666.666...\Omega = 6.66666... k\Omega = 6.67\Omega$$

**4 a** 5.7 cm ± 2% **b** 450 kg ± 0.4% **c** 10.6 s ± 0.5% **d** 366 000 J ± 0.3%

**5 a**  $1200 \pm 120 \text{ W}$  **b**  $330\ 000 \pm 1650 \ \Omega$ 

**6 D** 1400 ± 5 mm (Did you calculate them all? The same absolute error means the percentage error will be smallest in the largest measurement, so no need to calculate.)

## 2 Standard form and prefixes

**1 a** 1.35×10<sup>3</sup> W (or 1.350 × 10<sup>3</sup> W to 4 s.f.) **b** 1.3×10<sup>5</sup> Pa **c** 6.96×10<sup>8</sup> s **d** 1.76×10<sup>11</sup> C kg<sup>-1</sup>

2 a 2 260 000 J in 1 kg, so there will be 1000 times fewer J in 1 g:  $\frac{2260000}{1000} = 2260 \text{ J/g}$ 

**b** 1 kJ = 1000 J, 2 260 000 J/kg = 
$$\frac{2260000}{1000}$$
 kJ/kg = 2260 kJ/kg

**c** 1 MJ = 1000 kJ, so 2260 kJ/kg = 
$$\frac{2260}{1000}$$
 MJ/kg = 2.26 MJ/kg

**3 a** 2.5×10<sup>-3</sup> m **b** 1.60×10<sup>-15</sup> m **c** 1×10<sup>-8</sup> J **d** 5×10<sup>3</sup> m

**e**  $6.2 \times 10^{-1} \, \text{N}$ 

**4 a** 2.5 μm **b** 1.60 fm **c** 10 nJ **or** 0.01 μJ **d** 5 km

e 0.62 N or 62 cN

5 **a**  $0.009 \text{ m} = 9 \times 10^{-3} \text{ m} = 9 \text{ mm}$ 

**b**  $1 \times 10^{-5}$  m =  $1 \times 10 \times 10^{-6}$  m =  $10 \times 10^{-6}$  m =  $10 \mu m$  **c**  $4.7 \times 10^{-7}$  m =  $4.7 \times 100 \times 10^{-9}$  m =  $470 \times 10^{-9}$  m = 470 nm

**a** 64000000 **or** 6.4 × 10<sup>7</sup> **b** 99.99

**c** 800

**Physics** 

 $d 10^3$ 

7 **a**  $3.0 \times 10^8$  m s<sup>-1</sup> ÷  $3.03 \times 10^{-7}$  m =  $1.0 \times 10^{15}$  Hz

**b**  $3.0 \times 10^8 \text{ m s}^{-1} \div 1000 \text{ m} = 3.0 \times 10^5 \text{ Hz}$ 

**c**  $3.0 \times 10^8$  m s<sup>-1</sup> ÷  $1.0 \times 10^{-10}$  m =  $3.0 \times 10^{18}$  Hz

## 3 Resolving vectors

**Scalars:** density, electric charge, electrical resistance, energy, frequency, mass, power, temperature, voltage, volume, work done


Vectors: field strength, force, friction, momentum, weight

2 Scalars: 3 ms<sup>-1</sup>, 50 km, 273 °C, 50 kg, 3 A


**Vectors:**  $+20 \text{ ms}^{-1}$ , 100 m NE, -5 cm,  $10 \text{ km S } 30^{\circ}\text{W}$ ,  $3 \times 10^{8} \text{ m/s upwards}$ 

3 13 kN


4 Free body force diagram:




Triangle of forces:



5



6



**7 a** 5.0 N at 37° to the 4.0 N force

**b** 13 N at 23° to the 12.0 N force

# 4 Rearranging equations

1 
$$V = 12 \text{ V}$$
 and  $I = 0.25 \text{ A}$ 

$$V = I R$$
 so  $12 = 0.25 \times R$ 

$$R = \frac{V}{I} = \frac{12}{0.25} = 48 \,\Omega$$

2  $\lambda = 650 \text{ nm} = 650 \times 10^{-9} \text{ m} \text{ and } v = 3.0 \times 10^{8} \text{ m/s}$ 

**Physics** 

$$v = f \lambda$$
 so  $3.0 \times 10^8 = f \times 650 \times 10^{-9}$ 

$$f = \frac{v}{\lambda} = \frac{3.0 \times 10^8}{650 \times 10^{-9}} = 0.00462 \times 10^{17} = 4.62 \times 10^{14} \,\text{Hz}$$

3 
$$E = 4.01 \times 10^4 \text{ J}$$
 and  $m = 0.120 \text{ g} = 0.120 \text{ kg}$ 

$$E = mL \text{ so } 4.01 \times 10^4 = 0.120 \times L$$

$$L = \frac{E}{m} = \frac{4.01 \times 10^4}{0.120} = 334\,166\,\text{J/kg} = 3.34 \times 10^5\,\text{J/kg}$$
 in standard form

## 5 Work done, power, and efficiency

1 
$$22 \times 10^3 \text{ N} \times 2 \times 10^3 \text{ m} = 44\,000\,000 \text{ J} = 44 \text{ MJ}$$

$$2 \frac{62.5 \times 10^3 \text{ J}}{500 \text{ N}} = 125 \text{ m}$$

$$\frac{260\,000\,\text{N}\times25\,\text{m}}{48\,\text{s}} = 13\,541.6\,\text{W} = 14\,000\,\text{W} \text{ or } 14\,\text{kW} (2\,\text{s.f.})$$

$$4 \quad \frac{2500 \,\mathrm{N} \times 15 \,\mathrm{m}}{5 \,\mathrm{s}} = 7500 \,\mathrm{W} = 7.5 \,\mathrm{kW}$$

$$5 \quad \frac{8400}{11200} \times 100 = 75\%$$

$$6 \quad \frac{850}{1.2 \times 10^3} \times 100 = 71\%$$

$$7 \quad \frac{7.5}{8.0} \times 100 = 94\%$$